

## *Superfeed® 3 Linear Single*



Produced in Brazil, the feed horn **Superfeed® 3**, Linear Single, was designed for the reception of Band C with efficiency and practicality, for professional application in RX satellite systems. Compact and high efficiency model.



The feeder can be mounted on antennas with three or four rods, adapting to most models available on the market.



<b>Model</b>	<b>Superfeed 3 Single – BRSF3S</b>
<b>Polarization</b>	<b>Linear</b>
<b>Frequency Range</b>	<b>3.4 – 4.2 GHz</b>
<b>Rx Port</b>	<b>CPR 229F</b>
<b>F/D Range</b>	<b>0.31 to 0.40</b>
<b>VSWR</b>	<b>1.30:1 max.</b>
<b>Insertion Loss</b>	<b>0,20 dB</b>
<b>Return Loss</b>	<b>14 dB</b>
<b>Cross-polarization (Linear) on Axis</b>	<b>28 dB</b>
<b>Assembly</b>	<b>For primary focus antennas with 3 or 4 rods</b>
<b>Operating Temperature</b>	<b>-40°C to +60°C</b>
<b>Weight</b>	<b>1,3 Kg</b>
<b>Color</b>	<b>White</b>
<b>Painting</b>	<b>Electrostatic Epoxy</b>
<b>Accessories</b>	<b>Screws for LNB and scalar plate / flange protector</b>
<b>NCM</b>	<b>8529.10.90</b>

*Note: Specifications subject to change without notice.*

*Made in Brazil*